



Quality Changes The World

SYT125A(T6516-8)

SANY Tower Crane
三一重工塔式起重机




Better World Better SANY Crane

SANY CRANE



Jib Length & Tip Load 臂长组合及吊重 (1.6×1.6×2.5)/(1.6×1.6×2.8)





Transmission Mechanisms 传动机构

Transmission 传动	Legend 图例	Model 型号	Power 功率	Velocity 速度
Slewing 回转		HPZ55.130.195	2 × 5.5kW	0-0.7r/min
Trolleying 变幅		SXJ33.62P	4kW	0-60m/min
Hoisting 起升		SQJ04DPA	30kW	80/2 falls 40/4 falls
Voltage 电源电压	380V(±10%)		Frequency 电源频率	50Hz

Note: Contact with us when the rope capacity of hoisting mechanism is larger than 460m.
注：工作绳容量大于460m时请与厂家联系



Masts 塔身 B18F1 (1.6×1.6×2.5)

Anchorage 附着 (1.6×1.6×2.5)



Masts 塔身 (1.6×1.6×2.8)

Anchorage 附着 (1.6×1.6×2.8)



















Fixing 固定式

F1	Reactions in service 工作状态反力	126t
	Reactions out of service 非工作状态反力	161t
F2	Reactions in service 工作状态反力	88t
	Reactions out of service 非工作状态反力	125t
Freestanding height, dead weight at the max. jib (without counter weight, lifting weight nor ballast) 独立高度, 最长起重臂时自重 (不含平衡重、吊重、压重)		43t






Ballasting 压重式 Traveling 行走式

F3	Reactions in service 工作状态反力	73t
	Reactions out of service 非工作状态反力	83t
Freestanding height, dead weight at the max. jib (without counter weight, lifting weight nor ballast) 独立高度, 最长起重臂时自重 (不含平衡重、吊重、压重)		52t





Load Diagrams 起重特性表

radius/m 幅度 (m)	the max. capacity/t 最大起重量	18	20	22	25	28	30	32	35	38	40	42	45	48	50	52	55	58	60	63	65
65	 2.5-32.04m/4t				4.00				3.59	3.25	3.05	2.87	2.63	2.42	2.29	2.18	2.02	1.88	1.79	1.67	1.60
	 2.5-17.54m/8t	7.77	6.88	6.16	5.30	4.63	4.26	3.94	3.53	3.19	2.99	2.81	2.56	2.36	2.23	2.11	1.96	1.81	1.73	1.61	1.54
60	 2.5-33.41m/4t				4.00				3.78	3.42	3.21	3.02	2.77	2.55	2.42	2.30	2.14	1.99	1.90		
	 2.5-18.27m/8t	8.00	7.21	6.46	5.56	4.87	4.48	4.15	3.72	3.36	3.15	2.96	2.71	2.49	2.36	2.24	2.07	1.93	1.84		
55	 2.5-34.14m/4t				4.00				3.88	3.51	3.30	3.11	2.85	2.63	2.49	2.37	2.20				
	 2.5-18.66m/8t	8.00	7.39	6.62	5.71	4.99	4.60	4.26	3.82	3.45	3.24	3.04	2.79	2.56	2.43	2.30	2.14				
50	 2.5-34.22m/4t				4.00				3.89	3.52	3.31	3.12	2.86	2.63	2.50						
	 2.5-18.71m/8t	8.00	7.41	6.64	5.72	5.01	4.61	4.27	3.83	3.46	3.25	3.05	2.80	2.57	2.44						
45	 2.5-33.66m/4t				4.00				3.82	3.45	3.24	3.05	2.80								
	 2.5-18.41m/8t	8.00	7.27	6.51	5.61	4.91	4.52	4.19	3.75	3.39	3.18	2.99	2.74								
40	 2.5-33.30m/4t				4.00				3.77	3.41	3.20										
	 2.5-18.21m/8t	8.00	7.18	6.43	5.54	4.85	4.47	4.13	3.70	3.34	3.14										
35	 2.5-32.81m/4t				4.00				3.70												
	 2.5-17.95m/8t	7.98	7.06	6.33	5.45	4.76	4.39	4.06	3.64												
30	 2.5-31.25m/4t				4.00																
	 2.5-17.12m/8t	7.55	6.68	5.98	5.15	4.50	4.14														

Counter-jib Ballast 平衡臂及平衡重组合表

 (m)	 (m)	 (kg)	 2750kg	 1800kg
65	14.6	20100	6	2
60	14.6	18300	6	1
55	14.6	17350	5	2
50	14.6	16500	6	0
45	14.6	13750	5	0
40	14.6	11850	3	2
35	14.6	10050	3	1
30	14.6	9100	2	2

Packing List 运输部件

NO. 序号	Description 名称	Sketch 形状	L(m) 长	B(m) 宽	H(m) 高	Weight per unit (t) 单件重量 (t)	Quantity 数量
1	Jib section I 臂架 I		10.16	1.46	1.56	1.227	1
2	Jib section II 臂架 II		10.17	1.46	1.41	1.019	1
3	Jib section III 臂架 III		5.17	1.46	1.39	0.518	1
4	Jib section IV 臂架 IV		10.17	1.46	1.39	0.867	1

Packing List 运输部件

NO. 序号	Description 名称	Sketch 形状	L(m) 长	B(m) 宽	H(m) 高	Weight per unit (t) 单件重量 (t)	Quantity 数量
5	Jib section V 臂架 V		10.17	1.46	1.39	0.826	1
6	Jib section VI 臂架 VI		5.17	1.46	1.39	0.42	1
7	Jib section VII 臂架 VII		5.17	1.46	1.36	0.341	1
8	Jib section VIII 臂架 VIII		10.15	1.46	1.35	0.582	1
9	Tip jib 臂尖节		0.90	1.46	1.56	0.104	1
10	Tower head assembly 塔机总成		7.18	1.75	3.03	1.641	1
11	Counter jib 1 平衡臂节 1		4.78	1.46	0.69	0.745	1
12	Counter jib 2 平衡臂节 2		9.08	1.58	1.35	1.346	1
13	Telescoping cage 爬升架		6.28	3.62	5.67	3.21	1
14	Slewing assembly 回转总成		4.82	3.15	3.25	4.413	1
15	Transition mast assembly 过渡节		3.14	2.44	2.83	1.409	1
16	Standard mast 标准节		2.50	1.96	1.96	0.87	10
17	Strengthening mast 加强节		2.50	1.96	1.96	0.939	5
18	Basic mast 基础节		2.83	2.13	2.13	1.213	1
19	Trolley 小车		2.04	2.34	1.29	0.308	1
20	Hook 吊钩		1.06	0.25	1.54	0.296	1
21	Cabin 司机室		2.07	1.32	2.14	0.801	1
22	Hoisting mechanism 起升机构		2.18	1.5	0.96	1.45	1
23	Trolleying mechanism 变幅机构		1.11	0.56	0.58	0.35	1



SANY GROUP CRANE BU

SANY Tower Crane Industrial Park, No.168 Jinzhou Avenue, Jinzhou Development Zone, Changsha City, Hunan Province, P.R. China Zip 410600
Consulting sanycrane@sanygroup.com (Crane BU) / crd@sany.com.cn (IHQ)
After-sales Service 0086-400 6098 318

Reminder:

Any change in the technical parameters and configuration due to product modification or upgrade may occur without prior notice. The machine in the picture may include additional equipment. This brochure is for reference only, and goods in kind shall prevail.

Copyright at SANY. No part of this brochure may be copied or used for any purpose without written approval from SANY.

©Edited in November 2022 v1.0

三一集团起重事业部

中国湖南长沙金洲开发区金洲大道168号三一塔式起重机产业园 邮编: 410600
咨询: sanycrane@sanygroup.com (起重事业部) / crd@sany.com.cn (国际总部)
海外售后服务: 0086-400 6098 318

温馨提示:

由于技术不断更新, 技术参数及配置如有更改, 恕不另行通知。图中机器可能包括附加设备, 本画册仅供参考, 以实物为准。
版权为三一所有, 未经三一书面许可, 本画册任何内容不得被复制用于任何目的。

© 2022 年 11 月版

